



The Chemical Company

RHEOMAC[®] 730

Hydrophobic pore-blocking ingredient for watertight concrete

DESCRIPTION

RHEOMAC 730 is a hydrophobic pore-blocking ingredient (H.P.I) for concrete. It significantly reduces the water absorption of concrete.

RHEOMAC 730 is a chloride free organic admixture and supplied as a brown liquid. It reacts with the cement hydration process to form a hydrophobic ingredient to reduce the capillary suction and prevent the ingress of potentially deleterious soluble material, resulting in concrete with enhanced durability.

RECOMMENDED FOR

RHEOMAC 730 is suitable for any concrete structure, which requires watertightness, such as:

- Basement walls and floors
- Tunnels / underpasses
- Foundations, piles and pile caps
- Water retaining structures, swimming pool, water tanks, reservoirs, water towers
- Land drainage, manholes
- Reinforced concrete in a marine environment subject to tidal and wet/dry cycles
- Waste water treatment and desalination plant

FEATURES AND BENEFITS

Very low water absorption	Increased durability and water tightness
Integral system	Protection is maintained throughout the concrete mix
Ammonia free	Environmentally friendly. Fully compatible with certain surface coating and finishes

APPLICATION

Dispensing

RHEOMAC 730 should be added separately to the initial batching water to ensure complete distribution throughout the mix. Use only drinkable water – do not use seawater, bore water or water containing a high dissolved mineral content, for mixing concrete.

Curing

Like all cementitious products, concrete made with **RHEOMAC 730** must be protected against rapid drying due to high temperature and/or strong wind. The use of wet burlap, plastic sheets or a curing compound is highly recommended.

The optimum dosage for **RHEOMAC 730** to meet a specific requirement should always be determined by trial mixes.

Recommended dosage rate is 1.5 to 2.0 litres per 100 kg of cement. Other dosages may also be used depending on the specific requirements.

Consult local BASF Construction Chemicals Technical Sales Representative for assistance in determining dosage.

PACKAGING

RHEOMAC 730 is available in 1000 litre pallecons.

STORAGE

RHEOMAC 730 can be kept for 12 months from date of manufacture if stored in well protected area away from sunlight, at ambient temperate in dry conditions.

PRECAUTIONS

For the full health and safety hazard information and how to safely handle and use this product, please make sure that you obtain a copy of the BASF **Material Safety Data Sheet (MSDS)** from our office or our website.

DOSAGE



The Chemical Company

RHEOMAC[®] 730

ARmac730/2/0811

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this **BASF** publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by **BASF** either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not **BASF**, are responsible for carrying out procedures appropriate to a specific application.

BASF Australia Ltd
A.B.N. 62008437867
Head Office: 11 Stanton Road Seven Hills, NSW 2147
Ph. (02) 8811 4200

Newcastle	(02) 4961 3819
Canberra	(02) 6280 6010
Brisbane	(07) 3633 9900
Townsville	(07) 4774 7344
Melbourne	(03) 9549 0300

Adelaide	(08) 8139 7500
Perth	(08) 9366 2600
Darwin	(08) 8984 3269
Kalgoorlie	0417 772 355

BASF New Zealand Ltd
BASF WEB SITES

Head Office: 45 William Pickering Drive, Albany, Auckland Ph: (09) 414 7233
www.basf-cc.com.au www.basf-cc.co.nz www.meyco.basf.com
