



The Chemical Company

# FLOORKLEEN

Heavy duty emulsifiable cleaner

## DESCRIPTION

**FLOORKLEEN** is a ready to use low viscosity, heavy duty emulsifiable cleaner, comprising a blend of specially selected solvents and emulsifying agents. When scrubbed over the floor surface, it dissolves or brings into suspension, oil, grease, clear or pigmented solvent soluble coatings, curing compounds and various other contaminants which can then be readily scrub-rinsed away with clean water.

## RECOMMENDED FOR

- Removal of liquid membrane curing compounds and any concrete sealers from concrete floor surfaces prior to the application of a new surfacing material.
- Removal of spilt, blistered, or moisture affected clear lacquer type sealers.
- Eliminating oil, grease and grime, graffiti etc. from concrete, masonry, slate, metal, glass, ceramic tiles etc.
- Cleaning oily or greasy engines or other machinery.
- Cleaning tools and/or other equipment.

Not recommended for:

- Use on vinyl tiles, rubber flooring or other resilient floor coverings and most plastics.

## FEATURES AND BENEFITS

- **Effective on a wide range of solvent sensitive coatings and sealers**
- **Easy to apply with brush or broom**
- **Quick acting when protected from excessive evaporation**
- **Quickly and easily washed away with clean water**

## APPLICATION DIRECTIONS

Apply **FLOORKLEEN** liberally with a nylon or a bristle scrubbing brush or firm broom. Allow to stand for 3-5 minutes taking care to avoid excessive evaporation in hot conditions by covering area with polythene film, so as to maintain a wet **FLOORKLEEN** film in contact with the surface.

Pour on cold water or preferably hose down surface, while scrubbing firmly with scrubbing brush or firm broom. Continue until the rinse water no longer contains streaks of milky white colour.

Repeat the process if required until all traces of contaminants or sealers have been removed.

## ESTIMATING DATA

Depending on the texture of the surface to be cleaned and the nature of the film to be removed, allow 5-8 m<sup>2</sup>/litre.

## SHELF LIFE

Store in a cool, well ventilated, dry place away from open fires, stoves or naked flames. Under these conditions a shelf life of 24 months may be expected in tightly closed original containers.

## PACKAGING

**FLOORKLEEN** is available in 4 litre screwtop tins or 20 litre closed head pails.

## PRECAUTIONS

Read all Safety Directions and warnings on containers before use:

- **FLOORKLEEN** is flammable.
- DO NOT store or use near open fires, naked flames, stoves or operating electrical equipment.
- DO NOT smoke during application.
- Avoid skin contact, wear rubber or PVC gloves and goggles for eye protection.
- Provide plenty of ventilation so as to avoid breathing its vapour.
- Use approved mask or breathing apparatus in confined areas.
- Refer to Material Safety Data Sheet for full safety information.



The Chemical Company

# FLOORKLEEN

---

AFIk/3/1011

---

## STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this **BASF** publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

---

## NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by **BASF** either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not **BASF**, are responsible for carrying out procedures appropriate to a specific application.

---

### BASF Australia Ltd

A.B.N. 62008437867

Head Office: 11 Stanton Road Seven Hills, NSW 2147

Ph. (02) 8811 4200

Newcastle (02) 4961 3819

Canberra (02) 6280 6010

Brisbane (07) 3633 9900

Townsville (07) 4774 7344

Melbourne (03) 9549 0300

Adelaide (08) 8139 7500

Perth (08) 9366 2600

Darwin (08) 8984 3269

Kalgoorlie 0417 772 355

---

### BASF New Zealand Ltd

#### BASF WEB SITES

Head Office: 45 William Pickering Drive, Albany, Auckland Ph: (09) 414 7233

[www.basf-cc.com.au](http://www.basf-cc.com.au)

[www.basf-cc.co.nz](http://www.basf-cc.co.nz)

[www.meyco.basf.com](http://www.meyco.basf.com)

---