



The Chemical Company

MASTERSEAL® 155 PRIMER

Acrylic primer for MASTERSEAL 150 coating system

DESCRIPTION

MASTERSEAL 155 Primer is a water based acrylic primer used to prime mineral substrates prior to the application of MASTERSEAL top coats. (**MASTERSEAL 160, MASTERSEAL 150**)

RECOMMENDED FOR

MASTERSEAL 155 Primer is recommended for application to cementitious and other mineral substrates to seal the surface and provide improved adhesion for subsequent **MASTERSEAL 160** or **MASTERSEAL 155** coatings. Application of **MASTERSEAL 155 Primer** also eliminates differences in absorption which can give rise to irregularities to the final finish.

MASTERSEAL 155 Primer should only be used in conjunction with MASTERSEAL top coats.

SPECIFICATION

Supply form	Off white liquid
Specific gravity	1.3kg/L
Overcoating time (dependent on substrate & ambient conditions)	2-6 hours
Application Temperature	Min. 5°C Max. 35°C

APPLICATION DIRECTIONS

Surface Preparation

The substrate must be free of dirt, dust, grease, oil, mould release agents, bond breakers and any other contaminants that may interfere with adhesion.

It is recommended that application be carried out by a skilled applicator, who is totally conversant with our products and systems.

Use a Rolana or long nap lambswool roller, brush or spray gun.

Load roller or brush and apply an even coat, with only slight overlap, to avoid uneven drying of the finish coat. In general, the more absorbent the substrate, the more diluted is the **MASTERSEAL 155 Primer**.

High Absorption: Mix 1 part **MASTERSEAL 155 Primer** with 1 part water.

Medium Absorption: Mix 2 parts **MASTERSEAL 155 Primer** with 1 part water.

Low Absorption: Use **MASTERSEAL 155 Primer** undiluted.

CLEAN UP

Thoroughly clean equipment with water.

ESTIMATING DATA

Standard coverage is 0.08 litres/m² or 12.5m²L.

SHELF LIFE

MASTERSEAL 155 Primer has a 12 month shelf life if kept tightly closed in its original container at a moderate temperature, protected against direct sunlight.

PACKAGING

MASTERSEAL 155 Primer is available in 15 litre pails.

PRECAUTIONS

Exercise care when handling. Avoid contact with skin and eyes. If contact is made with skin, remove contaminated clothing, wash contacted area well with soap and water. If irritation persists seek medical aid. If in eyes do not rub in. Wash immediately with plenty of water.

If swallowed give a glass of water and seek immediate medical advice. Avoid inhalation of spray mists.

For the full health and safety hazard information and how to safely handle and use this product, please make sure that you obtain a copy of the BASF Construction Chemicals **Material Safety Data Sheet (MSDS)** from our office or our website.



The Chemical Company

MASTERSEAL® 155 PRIMER

AMseal155/7/1111

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this **BASF** publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by **BASF** either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not **BASF**, are responsible for carrying out procedures appropriate to a specific application.

BASF Australia Ltd

A.B.N. 62008437867

Head Office: 11 Stanton Road Seven Hills, NSW 2147

Ph. (02) 8811 4200

Newcastle (02) 4961 3819

Canberra (02) 6280 6010

Brisbane (07) 3633 9900

Townsville (07) 4774 7344

Melbourne (03) 9549 0300

Adelaide (08) 8139 7500

Perth (08) 9366 2600

Darwin (08) 8984 3269

Kalgoorlie 0417 772 355

BASF New Zealand Ltd

BASF WEB SITES

Head Office: 45 William Pickering Drive, Albany, Auckland Ph: (09) 414 7233

www.basf-cc.com.au

www.basf-cc.co.nz

www.meyco.basf.com
