

MASTERTOP[®] P PRIMER

Bonding agent for MASTERTOP floor levelling products

DESCRIPTION

MASTERTOP P Primer is an acrylic copolymer emulsion for priming and bonding of cementitious floor levelling compounds.

RECOMMENDED FOR

MASTERTOP P Primer is recommended for use as primer for cementitious floor levelling products.

FEATURES AND BENEFITS

- **Excellent adhesion to concrete**
- **As a pore sealer to prevent air bubbles rising through the applied levelling compound**
- **Can be diluted 1:3 by volume with water**
- **Easy to apply**
- **Fast application**

SPECIFICATIONS

Supply form	liquid
Colour	milky white
Specific gravity	1.06kg/litre
Viscosity	500 cP approx
pH value	8.0 approx
Solubility	can be mixed with water
Storage temperature	sensitive to frost
Application temperature	not below 5°C
Physiological effect	neutral
Toxicity	non toxic
VOC content*	63grams/litre

*Test method: SCAQMD method 304-91

ESTIMATING DATA

- One litre of **MASTERTOP P Primer** when diluted with 3 litres of water will prime approximately 25m²
- One litre of **MASTERTOP P Primer** when diluted with 2 litres of water will prime approximately 20m²
- One litre of **MASTERTOP P Primer** when diluted with 1 litre of water will prime approximately 15m²

APPLICATION

Substrate Condition

The substrate must be clean, sound and free of dust and loose particles. Cement laitance, oil, grease or curing compounds must be removed from concrete surfaces by grinding, scabbling, shot blasting or other means.

The temperature of the substrate should not be below 5°C. To avoid too high surface temperature, it is advisable to shade application areas.

Dilute as required, application can be by brush, roller or squeegee, ensure that the primer is applied evenly. Allow to dry prior to the application of the floor-levelling product. Rain damaged or very porous surfaces should be primed at least twice to enhance adhesion and to reduce air bubbles.

Note non porous substrates such as ceramic tiles, terrazzo etc should be primed with **MASTERTOP 1116** water based epoxy.

CURING

Drying time may vary depending on temperature and airflow.

GENERAL GUIDELINES

Do not work at temperatures below 5°C.

CLEANING

Tools should be cleaned with water before the material hardens.

SHELF LIFE

MASTERTOP P Primer has a shelf life of 12 months if stored in a cool, dry, well-ventilated area, out of direct sunlight in tightly closed original packaging, not below freezing point.

PACKAGING

MASTERTOP P Primer is available in 5L plastic jerry cans and 20L pails.

PRECAUTIONS

MASTERTOP P Primer is not toxic but may be irritating to skin and eyes. Wear safety glasses and gloves when handling. Wash off splashes with clean water. If irritation persists, seek medical advice.

For the full health and safety hazard information and how to safely handle and use this product, please make sure that you obtain a copy of the BASF Construction Chemicals **Material Safety Data Sheet (MSDS)** from our office or our website.



The Chemical Company

MASTERTOP[®] P PRIMER

AMtopPPrimer/4/1111

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this **BASF** publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by **BASF** either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not **BASF**, are responsible for carrying out procedures appropriate to a specific application.

BASF Australia Ltd
A.B.N. 62008437867
Head Office: 11 Stanton Road Seven Hills, NSW 2147
Ph. (02) 8811 4200

Newcastle	(02) 4961 3819
Canberra	(02) 6280 6010
Brisbane	(07) 3633 9900
Townsville	(07) 4774 7344
Melbourne	(03) 9549 0300

Adelaide	(08) 8139 7500
Perth	(08) 9366 2600
Darwin	(08) 8984 3269
Kalgoorlie	0417 772 355

BASF New Zealand Ltd
BASF WEB SITES

Head Office: 45 William Pickering Drive, Albany, Auckland Ph: (09) 414 7233
www.basf-cc.com.au www.basf-cc.co.nz www.meyco.basf.com
